FLAT EMULSION PAINTS, GENERAL SERIES

PRODUCT NUMBER 450 / 650 / 860

TYPE The matt emulsion paint based on excellent water resistant, alkali resistant

water-based resin with hiding pigment and additives.

USES Used for indoor cement, brick, gypsum structure to decoration and protection such as

office buildings, hotels, public places, hospitals, shops, houses etc.

CHARACTERISTICS 1. Use water as the solvent without pollution and fire danger.

2. Use water as a dilution to be able to reduce the construction cost.

3. Matt, hard film with smooth appearance.

4. Excellent resistance to water and alkalis.

GLOSS Flat

COLOR White or light colors

No.450 : Above 12.5 m²/L No.650 : Above 10.0 m²/L No.860 : Above 7.0 m²/L **HIDING POWER**

MASS DENSITY Above 1.3 Kg/L 80~110 KU (25°C) VISCOSITY

Set-to-touch 1/2 hr. Dry hard 2 hrs. (25°C) **DRYING TIME**

OPTIMUM FILM THICKNESS Wet 90 microns Dry 35 microns

42.0 m²/Gal 11.1 m²/L 8.5 m²/Kg THEORETICAL COVERAGE

OVERCOATING INTERVALS Min. 3 hrs. NON-VOLATILE CONTENT Above 50% **THINNER** Tap water

THINNING RATE 10~20%(depending on the coating method)

No.410-1 Emulsion Primer PRECEDING COATS

No.467 Water-based Penetrating Waterproof Sealer

STORAGE SHELF LIFE Minimum 2 years under normal storage conditions.

APPLICATION METHOD Spray, Brush, Roller.

NOTE 1. Before application, stir paint thoroughly, and when paint is too thick, the tap water within specified quantity can be added.

- 2. Adhered moisture, grease, and dirt on substrate must be cleaned thoroughly.
- 3. Do not use this paint to mix with other colored paints, if required, please use No.411~412 Acrylic Emulsion Paints to avoid color fading.
- 4. The application must be waited for 2 to 3 weeks until the walls were completely dry off and the moisture content under 12%, because the new constructed cement walls contain a lot of moisture and free alkaline substances that may reduce paint film performance and adhesion.

EPDM410860XX V1.1