READY-MIXED PAINT, DARK COLOR SERIES

PRODUCT NUMBER

101 / 106 / 107 / 108 / 110

TYPE

USES

CHARACTERISTICS

1. Good weather resistance and color retention.

Used for indoor or outdoor steel and wood structures.

The paints based on long oil alkyd resin with weather resistant pigments.

2. Excellent resistance to moisture and water.

3. Tough and hard film with good adhesion

4. Easy Application

GLOSS COLOR

HIDING POWER

Desired colors

Above 85%

No.101/110/106: Above 8 m²/L No.107/108 : Above 20 m²/L

MASS DENSITY VISCOSITY **DRYING TIME**

OPTIMUM FILM THICKNESS

THEORETICAL COVERAGE OVERCOATING INTERVALS

NON-VOLATILE CONTENT

HEAT RESISTANCE

THINNER THINNING RATE PRECEDING COATS Above 0.9 Kg/L 75~90 KU (25°C)

Set-to-touch 4 hrs. Dry hard 12 hrs. (25 °C)

Wet 80 microns Dry 35 microns 47.0 m²/Gal 12.5 m²/L 13.8 m²/Kg

Min. 10 hrs. (25°€)

Above 60%

Continuous 80 °C Intermittent 120 °C

No.805 Paint Thinner (OM-07) 5~10% (depends on tools used) 1. Wood: No.109 White Oil Primer

2. Steel: No.911 Red Oxide Primer (SP-70)

No.905/906 Red Lead Primer (OP-91/OP-92) No.992 Aluminum Tripolyphosphate Primer No.907 Zinc Chromate Primer (OP-93)

(or according to our specific method of application)

STORAGE SHELF LIFE APPLICATION METHOD

NOTE

Minimum 1 year under normal storage conditions.

Spray, Brush, Roller (Have to order roller type product for the roller application.)

- 1. Before application, stir paint evenly, and when paint is too thick, thinner within specified quantity can be added.
- 2. Adhered moisture, grease, dirt, damaged or loose old paint and corrosive salts on substrate must be cleaned thoroughly.
- 3. Avoid applying the paint in rainy, humid weather or substrate temperature excessively high to 40°C or low to 10°C.
- 4. Avoid applying to insufficient drying of previous paint coat.
- 5. The No.101 is not suitable as the color base that toned to become light-red, and the suggestion is use No.1707 to avoid color fading.
- 6. Don't use No.110 as the color base to avoid color fading.

EPDM010101XX V1.1

YUNG CHI PAINT & VARNISH MFG. CO., LTD.

No.26, Yen Hai 3rd Road, Kaohsiung, Taiwan. TEL:886-7-8713181 http://www.rainbowpaint.com.tw

FAX:886-7-8715443