READY-MIXED PAINT, WHITE COLOR SERIES

PRODUCT NUMBER 102 / 111

TYPE The paints based on long oil alkyd resin with weather resistant titanium dioxide.

USES Used for indoor or outdoor steel and wood structures.

CHARACTERISTICS 1. Good weather resistance and color retention.

2. Excellent resistance to moisture and water.

3. Tough and hard film with good adhesion

4. Easy Application

GLOSS Above 85%

COLOR White

No.102: Above 14.0 m²/L No.111: Above 10.0 m²/L HIDING POWER

Above 1.1 Kg/L MASS DENSITY 75~90 KU (25°C) **VISCOSITY**

Set-to-touch 4 hrs. Dry hard 12 hrs. $(25^{\circ}C)$ **DRYING TIME**

OPTIMUM FILM THICKNESS Wet 80 microns Dry 35 microns THEORETICAL COVERAGE 47.0 m²/Gal 12.5 m²/L 10.4 m²/Kg

Min. 10 hrs. (25°C) OVERCOATING INTERVALS

NON-VOLATILE CONTENT Above 56%

HEAT RESISTANCE Continuous 80 °C Intermittent 120 °C

No.805 Paint Thinner (OM-07) THINNER 5~10% (depends on tools used) THINNING RATE 1. Wood: No.109 White Oil Primer PRECEDING COATS

2. Steel: No.911 Red Oxide Primer (SP-70)

No.905/906 Red Lead Primer (OP-91/OP-92) No.992 Aluminum Tripolyphosphate Primer No.907 Zinc Chromate Primer (OP-93)

(or according to our specific method of application)

STORAGE SHELF LIFE Minimum 1 year under normal storage conditions. APPLICATION METHOD

Spray, Brush, Roller (Have to order roller type product for the roller application.)

- 1. Before application, stir paint evenly, and when paint is too thick, thinner within specified quantity can be added.
- 2. Adhered moisture, grease, dirt, damaged or loose old paint and corrosive salts on substrate must be cleaned thoroughly.
- 3. Avoid applying the paint in rainy, humid weather or substrate temperature excessively high to 40°C or low to 10°C.
- 4. Avoid applying to insufficient drying of previous paint coat.

EPDM010102XX V1.1

NOTE

YUNG CHI PAINT & VARNISH MFG. CO., LTD.

No.26, Yen Hai 3rd Road, Kaohsiung, Taiwan. TEL:886-7-8713181 http://www.rainbowpaint.com.tw

FAX:886-7-8715443