## READY-MIXED PAINT, WHITE COLOR SERIES

PRODUCT NUMBER 102 / 111

**TYPE** The paints based on long oil alkyd resin with weather resistant titanium dioxide.

**USES** Used for indoor or outdoor steel and wood structures.

**CHARACTERISTICS** 1. Good weather resistance and color retention.

2. Excellent resistance to moisture and water.

3. Tough and hard film with good adhesion

4. Easy Application

**GLOSS** Above 85%

**COLOR** White

No.102: Above 14.0 m<sup>2</sup>/L No.111: Above 10.0 m<sup>2</sup>/L HIDING POWER

Above 1.1 Kg/L MASS DENSITY 75~90 KU (25°C) **VISCOSITY** 

Set-to-touch 4 hrs. Dry hard 12 hrs.  $(25^{\circ}C)$ **DRYING TIME** 

**OPTIMUM FILM THICKNESS** Wet 80 microns Dry 35 microns THEORETICAL COVERAGE 47.0 m²/Gal 12.5 m<sup>2</sup>/L 10.4 m<sup>2</sup>/Kg

Min. 10 hrs. (25°C) OVERCOATING INTERVALS

NON-VOLATILE CONTENT Above 56%

**HEAT RESISTANCE** Continuous 80 °C Intermittent 120 °C

No.805 Paint Thinner (OM-07) THINNER 5~10% (depends on tools used) THINNING RATE 1. Wood: No.109 White Oil Primer PRECEDING COATS

2. Steel: No.911 Red Oxide Primer (SP-70)

No.905/906 Red Lead Primer (OP-91/OP-92) No.992 Aluminum Tripolyphosphate Primer No.907 Zinc Chromate Primer (OP-93)

(or according to our specific method of application)

STORAGE SHELF LIFE APPLICATION METHOD NOTE

Minimum 1 year under normal storage conditions.

Spray, Brush, Roller (Have to order roller type product for the roller application.)

- 1. Before application, stir paint evenly, and when paint is too thick, thinner within specified quantity can be added.
- 2. Adhered moisture, grease, dirt, damaged or loose old paint and corrosive salts on substrate must be cleaned thoroughly.
- 3. Avoid applying the paint in rainy, humid weather or substrate temperature excessively high to 40°C or low to 10°C.
- 4. Avoid applying to insufficient drying of previous paint coat.

EPDM010111XX V1.1

## YUNG CHI PAINT & VARNISH MFG. CO., LTD.

No.26, Yen Hai 3rd Road, Kaohsiung, Taiwan. TEL:886-7-8713181 http://www.rainbowpaint.com.tw

FAX:886-7-8715443