## RAINBOW SELF-PRIMERING TOPCOAT

PRODUCT NUMBER

**TYPE USES** 

**CHARACTERISTICS** 

**GLOSS** 

COLOR

**FLASH POINT HIDING POWER** MASS DENSITY VISCOSITY **DRYING TIME** 

**OPTIMUM FILM THICKNESS** THEORETICAL COVERAGE OVERCOATING INTERVALS NON-VOLATILE CONTENT

**HEAT RESISTANCE** 

**THINNER** THINNING RATE PRECEDING COATS

SUBSEQUENT COATS STORAGE SHELF LIFE APPLICATION METHOD

NOTE

155

Self-primering topcoat based on alkyd resin with non-pollution anti-corrosive pigment. Used for external steel frames and internal parts, the without pollution anti-corrosive primer also is a topcoat.

- 1. Good weather resistance and color retention.
- 2. Release of exceptionally strong in the chelating power of tripolyphosphate ions, excellent anti-corrosion, do not need to apply tradition primer before coating.
- 3. Excellent resistance to sea water and oils.
- 4. Excellent resistance to weather and abrasion.
- 5. Have anti-corrosive primer and topcoat of a dual nature.
- 6. Easy Application

Below 75%

#36 gray and #41 bluish grey

**25℃ (77**°F) Above 12.5 m<sup>2</sup>/L Above 1.0 Kg/L 70~90 KU (25°C)

Set-to-touch 4hrs. Dry hard 16 hrs. (25°C) Wet 80 microns Dry 35 microns  $12.5 \text{ m}^2/\text{Kg}$ 47.0 m²/Gal 12.5 m²/L

Min. 10 hrs. Above 60%

Continuous 80 °C Intermittent 120 °C

No.805 Paint Thinner (OM-07) 5~0% (depends on tools used) No.908 Wash Primer (SP-01/SP-02)

No.905 \ 906 Red Lead Primer (OP-91/OP-92)

Oleoresinous topcoats

Minimum 1 year under normal storage conditions.

Spray, Brush, Roller.

- 1. Before application, stir paint evenly, and when paint is too thick, thinner within specified quantity can be added.
- 2. Adhered moisture, grease, dirt, damaged or loose old paint and corrosive salts on substrate must be cleaned thoroughly.
- 3. Avoid applying the paint in rainy, humid weather or substrate temperature excessively high to 40°C or low to 10°C.
- 4. Avoid applying to insufficient drying of previous paint coat.
- 5. In order to enhance the effect of steel surface coating, please brush 2 times and dry paint film more than 70 microns, more can show the excellent dual nature.

EPDM010155XX V1.0

## YUNG CHI PAINT & VARNISH MFG. CO., LTD.

No.26, Yen Hai 3rd Road, Kaohsiung, Taiwan. TEL:886-7-8713181 http://www.rainbowpaint.com.tw

FAX:886-7-8715443