FLAT PAINT, WHITE

PRODUCT NUMBER 2301

TYPE Flat topcoat based on special synthetic resin with titanium dioxide pigment.

USES Used for ship's living place and house's or shop's indoor to decoration.

CHARACTERISTICS 1. Drying fast and excellent adhesion.

2. Soft and flat film.

3. Excellent resistance to moisture, water and salt water.

4. Tough film with excellent abrasion.

5. Easy application.

FINISH Flat White COLOR

Above 10 m²/L HIDING POWER MASS DENSITY Above 1.3 Kg/L VISCOSITY 70 ~ 90 KU (25°C)

Set-to-touch 1/2 hr. Dry hard 3 hrs. (25°C) **DRYING TIME**

OPTIMUM FILM THICKNESS Wet 100 microns Dry 40 microns

THEORETICAL COVERAGE 38.0 m²/Gal 10.0 m²/L $7.7 \text{ m}^2/\text{Kg}$

OVERCOATING INTERVALS Min. 4 hrs. NON-VOLATILE CONTENT Above 60%

No.805 Paint Thinner (OM-07) **THINNER** THINNER RATE 5 ~ 10% (tools cleaning excluded) PRECEDING COATS No.404 Solvent-based Acrylic Primer

No.410-1 Emulsion Primer

STORAGE SHELF LIFE Minimum 1 year under normal storage conditions.

APPLICATION METHOD Spray, Brush, Roller.

NOTE 1. Before application, stir paint evenly, and when paint is too thick, the thinner within

specified quantity can be added.

2. Adhered moisture, grease, and dirt on substrate must be cleaned thoroughly.

EPDM012301XX V1.0