



RAINBOW

SILVER BLANKET POLYURETHANE FOR WATER PROOF

PRODUCT NUMBER	783
TYPE	The polyurethane coating based on special polyol resin, polyisocyanate hardener with special pigments.
USES	Used for roofs, balconies, bathrooms, air garden etc.
CHARACTERISTICS	<ol style="list-style-type: none">1. Water proof and leak proof.2. Prevent cement for chalking and cracking.3. Film is soft and flexible.4. Good-looking and practical.
COLOR	Gray
VISCOSITY	4000 ~ 8000 cps (mixture, 25°C)
DRYING TIME	Set-to-touch 6 hrs. Dry hard 16 hrs. Fully cured 7 days
OPTIMUM FILM THICKNESS	Wet 1 ~ 2 mm Dry 1 ~ 2 mm
THEORETICAL COVERAGE	Average coating area of per set of 30 Kg are about 13.2 m ² . (reference value)
OVERCOATING INTERVALS	Min. 16 hrs. Max. 7 days (25°C)
MIXING RATIO	Base : Hardener = 24Kg : 6 Kg
NON-VOLATILE CONTENTS	Above 96%
POT LIFE	Above 1 hr. (mixture, 25°C)
THINNER	No.736 Polyurethane Thinner (cleaning tools only)
PRECEDING COATS	No.1062 Epoxy Primer For Water Proof, Solvent Base No.785 Moisture-cured Polyurethane Primer For Water Proof
SUBSEQUENT COATS	No.781 Weather Resistant Polyurethane Top Coating For Water Proof
STORAGE SHELF LIFE	Minimum 1 year under normal storage conditions.
APPLICATION METHOD	Trowel
NOTE	<ol style="list-style-type: none">1. Adhered moisture, grease, dust and rust on substrate must be cleaned thoroughly.2. Mix base and hardener according to the mixing ratio and stir thoroughly.

YUNG CHI PAINT & VARNISH MFG. CO., LTD.

No.26, Yen Hai 3rd Road, Kaohsiung, Taiwan.
<http://www.rainbowpaint.com.tw>

TEL:886-7-8713181
FAX:886-7-8715443