



RAINBOW

SOLVENT-BASED ACRYLIC PAINT, CLEAR

PRODUCT NUMBER	402
TYPE	The solvent-based clear paint based on weather and alkali resistant acrylic resin.
USES	Used for protection of cement wall colored solvent-based acrylic paint, gypsum or marl products.
CHARACTERISTICS	<ol style="list-style-type: none">1. Fast drying and very good workability2. Excellent water, weather resistance, and gloss retention.3. Excellent adhesion to cement or gypsum or marl products.4. Excellent resistance to alkalis.
APPEARANCE	Transparent liquid
MASS DENSITY	Above 0.9 Kg/L
DRYING TIME	Set-to-touch 1/2 hr. Dry hard 2 hrs. (25°C)
OPTIMUM FILM THICKNESS	Wet 80 microns Dry 25 microns
THEORETICAL COVERAGE	47.0 m ² /Gal 12.5 m ² /L
OVERCOATING INTERVALS	Min. 3 hrs.
NON-VOLATILE CONTENT	Above 50%
THINNER	NO.807 Xylene
THINNING RATE	0~5%
STORAGE SHELF LIFE	Minimum 1 year under normal storage conditions.
APPLICATION METHOD	Spray, Brush, Roller.
NOTE	<ol style="list-style-type: none">1. The moisture content of new constructed cement walls should be under 12% . If not, the application must wait for 2 or 3 weeks until the wall is dry completely. Otherwise, too much moisture and alkali may affect film's performance and adhesion.2. Adhered moisture, grease, and dirt on substrate must be cleaned thoroughly.

EPDM040402XX V1.1

YUNG CHI PAINT & VARNISH MFG. CO., LTD.

No.26, Yen Hai 3rd Road, Kaohsiung, Taiwan.
<http://www.rainbowpaint.com.tw>

TEL:886-7-8713181
FAX:886-7-8715443